|  | IE & ' |   | $M \geq M$ |  |
|--|--------|---|------------|--|
|  |        | 1 |            |  |

| PARAMETERS        | USA   |
|-------------------|---|
| Engine Type       | Inline twin cylinder, 4 stroke, SOHC                        |
| Displacement      | 648cc   |
| Compression ratio | 9.5:1   |
| Max power         | 47.4 PS (34.9 kW) @ 7150 rpm                                |
| Max torque        | 56.5 Nm @ 5150 rpm  |
| Idle RPM          | 1200 ± 100 rpm  |
| Ignition          | Digital spark ignition                                      |
| Lubrication       | Forced lubrication, Wet sump with pump driven oil delivery  |
| Engine Oil        | 10W-50 to API SL (or higher) JASO MA2,<br>(Fully synthetic) |
| Clutch            | Wet multi plate   |
| Gear box          | 6 Speed constant mesh                                       |

## **CHASSIS & SUSPENSION**

| PARAMETERS         |                                    |  |
|--------------------|------------------------------------|--|
| Frame              | Steel tubular, double cradle frame |  |
| Front Suspension   | Upside down telescopic fork 43mm   |  |
| Front wheel travel | 130mm                              |  |
| Rear Suspension    | Twin shock                         |  |
| Rear wheel travel  | 115mm                              |  |

## **DIMENSIONS & WEIGHTS**

| PARAMETERS                    |                  |
|-------------------------------|------------------|
| Wheel Base                    | 57.5" (1460 mm)  |
| Ground Clearance              | 7.2" (184 mm)    |
| Length                        | 85.8" (2180 mm)  |
| Width                         | 33.7" (855 mm)   |
| Height                        | 45.67" (1160 mm) |
| Wet Weight (90% Fuel and oil) | 476 lbs (216 kg) |
| Max Weight Capacity           | 880 lbs (400 kg) |
| Fuel tank capacity            | 3.6* gal L       |

| BRAKES & TIRES                 |                                 |  |
|--------------------------------|---------------------------------|--|
| PARAMETERS                     |                                 |  |
| Brake System                   | Dual Channel ABS, Switchable    |  |
| Front                          | 320 mm disc, ABS                |  |
| Rear                           | 270 mm disc, ABS                |  |
| Front Tire (Spoked Wheel)      | 100/90-19 M/C 57H MRF NYLOREX-F |  |
| Rear Front Tire (Spoked Wheel) | 140/80R17 M/C 69H MRF NYLOREX-X |  |

## TIRE PRESSURE

| PARAMETERS | SOLO   | WITH PILLION |
|------------|--------|--------------|
| Front      | 32 psi | 32 psi       |
| Rear       | 36 psi | 42 psi       |

## **ELECTRICALS**

| PARAMETERS                |   |  |
|---------------------------|---|--|
| System                    | 12V - DC  |  |
| Battery                   | 12V - 12 Ah VRLA  |  |
| Head Lamp                 | LEAD Headlamp   |  |
| Tail lamp & BRAKE LAMP    | LED   |  |
| License plate illuminator | LED   |  |
| Turn Signals              | LED - Front & Rear  |  |
| Instrument Cluster        | Tripper Dash - 4 Inch round TFT Display with phone connectivity, Full Map Navigation (Powered by Google Maps), Media Controls |  |
| Charger port              | USB 2.0 Type C 5 V 2 A output   |  |
|                           | ENGINE OIL  |  |
| PARAMETERS                |   |  |
| Engine Oil                | 10W-50 to API AL (or higher) JASO MA2,<br>(Fully synthetic)   |  |
| Oil Capacity              | 1st Dry fill - 3.9 L<br>Refill - 3.1 L  |  |