ROYALENFIELD.COM





















COLOURWAYS



TOKYO BLACK



LONDON RED



REBEL BLUE



DAPPER GREY



RIO WHITE



FACTORY BLACK

SPECIFICATIONS

TOP AND MID

ENGINE

TYPE SINGLE CYLINDER, 4 STROKE, AIR-OIL COOLED

DISPLACEMENT 349CC

BORE X STROKE 72 MM X 85.8 MM

COMPRESSION RATIO 9.5:1

MAXIMUM POWER 20.2 BHP @ 6100 RPM (14.87 KW)

MAXIMUM TORQUE 27 NM @ 4000 RPM

IGNITION SYSTEM ELECTRONIC FUEL INJECTION (EFI) (CONTI)

CLUTCH WET, MULTI-PLATE

GEARBOX 5 SPEED CONSTANT MESH

LUBRICATION WET SUMP, FORCED LUBRICATION

ENGINE OIL SAE 15 W 50 API, SL GRADE, JASO MA 2 SEMI SYNTHETIC

AIR CLEANER PAPER ELEMENT ENGINE START ELECTRIC

CHASSIS AND SUSPENSION

TYPE TWIN DOWNTUBE SPINE FRAME

FRONT SUSPENSION TELESCOPIC, 41MM FORKS, 130MM TRAVEL

REAR SUSPENSION TWIN TUBE EMULSION SHOCK ABSORBERS WITH 6-STEP ADJUSTABLE PRELOAD

(90MM TRAVEL)

DIMENSIONS

WHEELBASE 1370 MM
GROUND CLEARANCE 160 MM
LENGTH 2055 MM

WIDTH 810 MM (WITHOUT MIRRORS)
HEIGHT 1070 MM (WITHOUT MIRRORS)

SEAT HEIGHT * 790 MM

KERB WEIGHT 181 KG (WITH 90% FUEL & OIL)

FUEL CAPACITY 13 LTR

BRAKES AND TYRES

TYRES FR.

ALLOY WHEEL- IIO/70-17" 54P (TUBLESS TYRE)

TYRES RR.

ALLOY WHEEL - I4O/70 - I7" 66P (TUBELESS TYPE)

BRAKES FRONT

300 MM DISC WITH TWIN PISTON FLOATING CALIPER

BRAKES REAR

270 MM DISC, SINGLE PISTON FLOATING CALIPER

ABS DUAL CHANNEL ABS

ELECTRICALS

ELECTRICAL SYSTEM 12 VOLT - DC

BATTERY 12 VOLT, 8 AH, VRLA (MAINTENANCE FREE)

HEAD LAMP

HB/LB: 12V, 16.5W/IIW (LED) WITH INTEGRATED FPL 12V, 1.65W(LED)

TAIL LAMP

TAIL/STOP: 13.5V, 0.5W/4.8W (LED)

TURN SIGNAL LAMP

12V, 10W X 2 PAIRS [FRONT & REAR]

PILOT LAMP

INTEGRATED WITH HEADLAMP

CLUSTER

DIGI-ANALOG (KMPH) (SINGLE SCALE)

USB CHARGER - TYPE-C FAST CHARGING

FLASHER RELAY 2 PIN
NEUTRAL SWITCH YES
GEAR POSITION SENSOR YES

SPECIFICATIONS

BASE

ENGINE

TYPE SINGLE CYLINDER, 4 STROKE, AIR-OIL COOLED

DISPLACEMENT 349CC

BORE X STROKE 72 MM X 85.8 MM

COMPRESSION RATIO 9.5:1

MAXIMUM POWER 20.2 BHP @ 6100 RPM (14.87 KW)

MAXIMUM TORQUE 27 NM @ 4000 RPM

IGNITION SYSTEM ELECTRONIC FUEL INJECTION (EFI) (CONTI)

CLUTCH WET, MULTI-PLATE

GEARBOX 5 SPEED CONSTANT MESH

LUBRICATION WET SUMP, FORCED LUBRICATION

ENGINE OIL SAE 15 W 50 API, SL GRADE, JASO MA 2 SEMI SYNTHETIC

AIR CLEANER PAPER ELEMENT ENGINE START ELECTRIC

CHASSIS AND SUSPENSION

TYPE TWIN DOWNTUBE SPINE FRAME

FRONT SUSPENSION TELESCOPIC, 41MM FORKS, 130MM TRAVEL

REAR SUSPENSION TWIN TUBE EMULSION SHOCK ABSORBERS WITH 6-STEP ADJUSTABLE PRELOAD

(90MM TRAVEL)

DIMENSIONS

WHEELBASE 1370 MM
GROUND CLEARANCE 160 MM
LENGTH 2055 MM

WIDTH 810 MM (WITHOUT MIRRORS)
HEIGHT 1070 MM (WITHOUT MIRRORS)

SEAT HEIGHT * 790 MM

KERB WEIGHT 181 KG (WITH 90% FUEL & OIL)

FUEL CAPACITY 13 LTR

BRAKES AND TYRES

TYRES FR. SPOKE WHEEL - 100/80 - 17" - 52P (TUBE TYPE)

TYRES RR. SPOKE WHEEL - 120/80 - 17" - 61P (TUBE TYPE)

BRAKES FRONT 300 MM DISC WITH TWIN PISTON FLOATING CALIPER

BRAKES REAR 153 MM DRUM, SINGLE LEAD INTERNAL EXPANDING

ABS SINGLE CHANNEL ABS

ELECTRICALS

ELECTRICAL SYSTEM 12 VOLT - DC

BATTERY
I2 VOLT, 8 AH, VRLA (MAINTENANCE FREE)
HEAD LAMP
HB/LB: I2V, HSI-35/35W (HALOGEN)
TAIL LAMP
TAIL/STOP: I2V, 2I/5W [BULB]
TURN SIGNAL LAMP
I2V, IOW X 2 PAIRS [FRONT & REAR]

PILOT LAMP NA

CLUSTER DIGI-ANALOG (KMPH) (SINGLE SCALE)

USB CHARGER TYPE-C PORT FLASHER RELAY 2 PIN NEUTRAL SWITCH YES GEAR POSITION SENSOR NO



MACHINE LOVE

SERVICE COST CALCULATOR

Plan ahead. Get the estimated service cost for your motorcycle before you book the appointment.



ROADSIDE ASSISTANCE

Get peace of mind wherever you're headed with on-site support for your motorcycle.



SPARES, ESSENTIALS, OILS & LUBES

Choose from our widely available range of Royal Enfield Spare Parts, Essentials, Oils, and Lubes, and keep your motorcycle riding at its best.



EXTENDED WARRANTY

Avail up to two additional years of complete coverage on all repairs, replacements and maintenance.



SERVICE BOOKING ON ROYAL ENFIELD APP

Book your motorcycle service appointment anytime, anywhere via the Royal Enfield app.



LABOUR ANNUAL MAINTENANCE CONTRACT

In addition to having all your labour costs covered as part of your scheduled service, get 10% off on all additional labour costs and 5% off on all spare parts.

LINTING 111// ROYAL ENFIELD

Some of the components and accessories featured in the photographs may not be a part of the standard fitment and applicable for all markets. For any queries, call us at 18002100007 or email us at support@royalenfield.com







Royal Enfield Royal Enfield