SCRAM!

ROYAL ENFIELD

SCRAM!

SCRAM 440 - INDIA

ENGINE

TYPE

Single cylinder, 4 stroke, SOHC, air-cooled, fuel injection

BORE X STROKE (IN MM)

81 x 86 mm

DISPLACEMENT

443 CC

FUEL INJECTION

Electronic Fuel Injection

COMPRESSION RATIO

9.5:1

IDLE RPM

1300 rpm

STARTING SYSTEM

Electric Start

MAXIMUM TORGUE

34 Nm @ 4000 rpm

CLUTCH

Wet Multi Plates

GEARBOX

6 Speed

LUBRICATION


Wet Sump

MAXIMUM POWER

25.4 Bhp (18.7 KW @ 6250 rpm)

ENGINE OIL GRADE

SEMI SYNTHETIC SAE 15W 50 API SL GRADE JASO MA 2



SCRAM!

CHASSIS & SUSPENSION

TYPE

Half-Duplex Split Cradle Frame

FRONT SUSPENSION

Telescopic, 41mm forks

FRONT WHEEL TRAVEL

190 mm travel

REAR SUSPENSION

Monoshock with linkage

REAR WHEEL TRAVEL

180 mm wheel travel

DIMENSIONS & WEIGHTS

WHEELBASE

1460mm

GROUND CLEARANCE

200mm

SEAT HEIGHT

795 mm

LENGTH

2165mm

WIDTH

840mm

HEIGHT

1170mm (without mirrors)

PAYLOAD WITH STANDARD EQUIPMENT

179 Kg

FUEL CAPACITY

15L

DRY WEIGHT

187 Kg (Alloy / Spoke)

KERB WEIGHT (90% FUEL + OIL)

196 Kg (Alloy / Spoke)

SCRAM!

BRAKES & TYRES

WHEEL TYPE	TYRE TYPE	ABS
Spoke / Alloys	Tube / Tubeless	Dual Channel, Switchable at rear

TYRES FR.	TYRES RR.
100/90 - 1 9" - dual-purpose tyres	120/90 - 17" - dual purpose tyres

BRAKES FRONT

Hydraulic Disc Brake 300 mm disc, 2-piston floating caliper

BRAKES REAR


Hydraulic Disc Brake 240 mm disc, single piston floating caliper

ELECTRICALS

ELECTRICAL SYSTEM	HEAD LAMP	TAIL LAMP
12V	14/12W LED	LED

TURN SIGNAL LAMP	OTHER EQUIPMENT	CLUSTER
12V, 10W	USB Charger - Type A	Digital - Analogue cluster

NAVIGATION	BATTERY
Tripper Pod (Optional)	12 V, 8 Ah Maintenance Free



ROYAL ENFIELD